

DESCRIPTION

AMC MODEL DVAT-0518-60-8-SK-196 IS A 0.5 TO 18 GHz VARIABLE ATTENUATOR/MODULATOR WITH 8 BIT BINARY TTL CONTROL OR OPTIONAL ANALOG VOLTAGE CONTROL.

SPECIFICATIONS



- FREQUENCY RANGE: 0.5 TO 18 GHz
- INSERTION LOSS: 4.5 dB MAXIMUM
- ATTENUATION FLATNESS:
 - ◎ 10 dB = ± 1.0 dB
 - ◎ 20 dB = ± 1.5 dB
 - ◎ 40 dB = ± 3.0 dB
 - ◎ 60 dB = ± 5.5 dB
- ATTENUATION ACCURACY:
 - 0-30 dB = ± 1.0 dB
 - 30-50 dB = ± 1.3 dB
 - 50-60 dB = ± 1.5 dB
- MONOTONICITY: GUARANTEED
- TEMPERATURE VARIATION:
 - ± 2.5dB -10 to 85 deg C Typ
 - ± 3.5dB -40 to 95 deg C Typ
- SWITCHING TIME: 1.5 micro sec MAXIMUM
- SMALL SIGNAL BANDWIDTH: 150 kHz Typ (6dB with ±3 dB sinewave)
- LARGE SIGNAL BANDWIDTH: 75 kHz Typ (30dB with ±30 dB sinewave)
- RETURN LOSS: -12 dB TYP -8.5 dB MAX
- POWER RATING: +20 dBm (see note 1)
- DIGITAL CONTROL: 8 BIT TTL
 - 0.25 dB MINIMUM ATTENUATION STEP
- ANALOG CONTROL option: 0-6V ANALOG VOLTAGE, 10dB/VOLT
- POWER SUPPLY: +12V OR +15V @ 150 mA MAXIMUM
- NEGATIVE SUPPLY IS OPTIONAL: 0 TO -15V @ 2 mA MAXIMUM (may be omitted)
- CONNECTORS
 - RF INPUT/OUTPUT: FIELD REPLACEABLE SMA (FEMALE)
 - POWER AND CONTROLS: 15 PIN MICRO-D FEMALE MATING CONNECTOR (MALE) FURNISHED
- SIZE: 2.00" x 1.81" x 0.50"

ENVIRONMENTAL RATINGS

- TEMPERATURE: -40°C TO +85°C (OPERATING)
-65°C TO +125°C (STORAGE)
- HUMIDITY: MIL-STD-202F, METHOD 103B COND. B
- SHOCK: MIL-STD-202F, METHOD 213B COND. B
- VIBRATION: MIL-STD-202F, METHOD 204D COND. B
- ALTITUDE: MIL-STD-202F, METHOD 105C COND. B
- TEMPERATURE CYCLE: MIL-STD-202F, METHOD 107D COND. A

ALL DIMENSIONS ARE IN INCHES
TOLERANCES:
X.XX ±0.010
X.XXX ±0.005

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	Original Release	08/08/07	
	A	SEE ECR# 09-004	1/22/09	



NOTES

1. Low Frequency reduced power performance refer to test report.
2. Negative supply only for compatability with previous models.
3. Negative supply may be -V, or Ground or Open Circuit.
4. SPECIFICATIONS WILL VARY OVER OPERATING TEMPERATURE.
5. SPECIFICATIONS SUBJECT TO CHANGE OR REVISION.

AMERICAN MICROWAVE CORPORATION

7311-G GROVE ROAD
FREDERICK, MARYLAND 21704 USA
TEL: 301-662-4700 FAX: 301-662-4938
WEBSITE: www.americanmicrowavecorp.com
E-MAIL: sales@americanmicrowavecorp.com
ISO 9001:2000 CERTIFIED





APPROVALS		DATE	TITLE			
DRAWN <i>JK</i>		08/08/07	PRODUCT FEATURE DVAT-0518-60-8-SK-196 OPTION: 0.5-18 GHz, VARIABLE ATTENUATOR			
CHECKED			SIZE	FSCM NO.	DWG NO.	REV.
ISSUED			A	60483	100-D001-001	A
			SCALE	N:S		SHEET 1 OF 4

DESCRIPTION

AMC MODEL DVAT-0518-60-8-SK-196 IS A 0.5 TO 18 GHz VARIABLE ATTENUATOR/MODULATOR WITH 8 BIT BINARY TTL CONTROL OR OPTIONAL ANALOG VOLTAGE CONTROL.

REVISIONS				
ZONE	REV.	DESCRIPTION	DATE	APPROVED
	-	Original Release	08/03/07	
	A	SEE ECR# 09-004	1/22/09	

MECHANICAL OUTLINE



STANDARD PIN NUMBERING	
PIN	FUNCTION
8	GND
7	Option: Latch En
6	Option: Analog I/P
5	GND
4	0.25 dB (LSB)
3	0.5 dB
2	1 dB
1	2 dB
15	4 dB
14	8 dB
13	16 dB
12	32 dB (MSB)
11	+12 to + 15V DC
10	-0.0 to - 15V DC
9	Not Used

AMERICAN MICROWAVE CORPORATION

7311-G GROVE ROAD
 FREDERICK, MARYLAND 21704 USA
 TEL: 301-662-4700 FAX: 301-662-4938
 WEBSITE: www.americanmicrowavecorp.com
 E-MAIL: sales@americanmicrowavecorp.com
 ISO 9001:2000 CERTIFIED



ALL DIMENSIONS ARE IN INCHES
 TOLERANCES:
 X.XX ±0.010
 X.XXX ±0.005

APPROVALS		DATE	TITLE			
DRAWN <i>JK</i>		08/03/07	MECHANICAL OUTLINE DVAT-0518-60-8-SK-196 OPTION: 0.5-18 GHz, VARIABLE ATTENUATOR			
CHECKED			SIZE	FSCM NO.	DWG NO.	REV.
			A	60483	100-D001-001	A
ISSUED			SCALE N:S			SHEET 2 OF 4